

WEITACK® Terpene Resin T120

Properties:

T120 is 100% pure terpene resin, used for Tapes, PSA, HMA. It is suitable for preparing adhesive mainly made from SIS. Has excellent compatibility with the thermoplastic elastomer SIS, SBS, SEBS, natural rubber. many kinds of synthetic rubber, EVA, as well as other tackifier resin

Detailed Specification:

Color (Gardner 1:1)	6 Max.	ASTM D 1544
Softening Point (Ring & Ball, 'C)	115-125	ASTM E 28
Acid Value (KOHmg/g)	1.0 Max.	ASTM D 974
Toluene insoluble substance %	0.05 Max.	

Typical Datas:

Color (Gardner 1:1)	5.	ASTM D 1544
Softening Point (Ring & Ball, 'C)	123	ASTM E 28
Acid Value (KOHmg/g)	0.17	ASTM D 974
Toluene insoluble substance %	0.029	

Application: Hot melt pressure sensitive adhesive
Hot melt adhesive , solvent based pressure sensitive adhesive

Packing: 25kg Kraft bags , 500kg big bags
1x20fcl = 16mts without pallets and 14mts with pallets for 25kg kraft bags
1x20fcl = 10mts for 500kg big bags

Storage:

Keep resin in ventilation place and away from heater, Temperature not exceeding 30'C is recommended in warehouse or during transportation, otherwise resins beads perhaps got lump.

Notice:

This product information is indicative and does not include any guarantee.

ADD: 603-1-3 , NO.63, MIDDLE HONGKONG ROAD, QINGDAO 266071, CHINA

TEL: 86-532-85721337, 85720052

Email: sales@weichemresin.com www.weichemresin.com